

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

GHS Product Code: C005-1-0C0  
 Product Name: CORCHEM® 5 Xylene [Xylol]  
 Recommended use: INDUSTRIAL PROTECTIVE COATING/LINING  
 Restrictions on use: INTENDED FOR PROFESSIONAL USE ONLY  
 Manufacturer: CORCHEM MANUFACTURING, INC.  
 Address: 1227 SOUTH MURPHY STREET  
 ODESSA TEXAS, USA 79766-8811  
 Emergency phone: INFOTRAC: +1-352-323-3500 (TOLL-FREE IN THE US: 800-535-5053)  
 Revision: 3-10222014

### SECTION 2: HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

##### OSHA Hazards

Flammable liquid, Carcinogen, Target Organ Effect, Harmful by skin absorption. Irritant

##### Target Organs

Liver, Kidney, Blood, Eyes, Ears, Heart, Bone marrow  
 Central nervous system

##### GHS Classification

Category 1 Serious eye damage  
 Category 2 Skin irritation  
 Acute aquatic toxicity  
 Category 3 Flammable liquids  
 Category 4 Acute toxicity, Inhalation  
 Acute toxicity, Dermal  
 Category 5 Acute toxicity, Oral

##### GHS Label elements, including precautionary statements

##### Hazard Pictograms



Signal word: **Danger**

##### GHS Hazard statement(s)

H226 Flammable liquid and vapor  
 H303 May be harmful if swallowed  
 H312 + H332 Harmful in contact with skin or if inhaled  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage  
 H401 Toxic to aquatic life

**NFPA Rating**

**HMIS**

|    |                     |
|----|---------------------|
| 2* | Health              |
| 3  | Flammability        |
| 0  | Physical Hazard     |
| J  | Personal Protection |

| PERSONAL PROTECTION INDEX |  |   |   |
|---------------------------|--|---|---|
| A                         |  | G |   |
| B                         |  | H |   |
| C                         |  | I |   |
| D                         |  | J |   |
| E                         |  | K |   |
| F                         |  | X | Consult your supervisor or S.O.P. for "SPECIAL" handling directions |
| A                         |  | n |   |
| t                         |  | o |   |
| u                         |  | p |   |
| w                         |  | q |   |
| y                         |  | r |   |
| z                         |  | s |   |
| Additional Information    |  |   |   |



**2012 ERG GUIDEBOOK # 130**

## GHS Precautionary statement(s)

|                    |  |
|--------------------|--|
| P102               | Keep out of reach of children  |
| P103               | Read label before use  |
| P202               | Do not handle until all safety precautions have been read and understood   |
| P210               | Keep away from heat/ sparks/ open flames/ hot surfaces. – No Smoking   |
| P260               | Do not breathe dust/ fumes/ gas/ mist/ vapors/ spray/  |
| P264               | Wash skin thoroughly after handling.   |
| P270               | Do not eat, drink or smoke when using this product.  |
| P271               | Use only outdoors or in a well-ventilated area.  |
| P273               | Avoid release to the environment.  |
| P280               | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

---

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

|  | <u>Ingredient(s)</u> | <u>CAS No.</u> | <u>Concentration</u> |
|--|----------------------|----------------|----------------------|
|  | Ethyl Benzene        | 100-41-4       | >30                  |
|  | Xylene               | 1330-20-7      | <100                 |

---

## SECTION 4: FIRST AID MEASURES

---

### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If not breathing, if breathing is irregular, or if respiratory arrest occurs, artificial respiration or oxygen should be administered by trained personnel only. It may be dangerous to provide mouth-to-mouth resuscitation. Keep person warm and quiet; seek immediate medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain open airway. Loosen tight clothing such as a collar, tie, belt, or waistband. Get medical attention if adverse health effects persist or are severe.

### Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, initiate and maintain continuous irrigation until patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Cover wound with sterile dressing, seek immediate medical attention. If skin is not damaged and symptoms persist, avoid further exposure, seek medical attention. Launder clothing before reuse.

### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 30 minutes while holding eyelids open; seek immediate medical attention.

### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### Protection of first aid personnel

No action shall be taken involving any personal risk without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, wear gloves.

### Notes to Physicians or First Aid providers

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested.

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

### Conditions of flammability

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

### Suitable extinguishing media

Alcohol-resistant foam, water-fog, carbon dioxide, dry chemicals, dry sand, limestone powder.

### Specific hazards and by-products from combustion

Decomposition products may be toxic and include the following materials: carbon dioxide, carbon monoxide, and various hydrocarbons. Fumes and vapors from the thermal and chemical decompositions vary widely in combustion and toxicity.

### Special protective equipment and precautions for fire-fighters

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

### Flash point

Estimated: Closed Cup: 77°F (25°C) – closed cup

### Explosive limit

Lower Explosive Limit: 1.1%(V), Upper Explosive Limit: 7%(V)

### Autoignition temperature


980° F (527° C)

### Fire and explosion hazards

In a fire or if heated, a pressure increase will occur and the container may burst.

### NFPA Rating

|               |   |
|---------------|---|
| Health:       | 2 |
| Flammability: | 3 |
| Reactivity:   | 0 |
| Special:      |   |



---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

### Personal Precautions

No action shall be taken involving personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear appropriate personal protective equipment (see section 8).

### Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air).

### Small Spill

Stop leak if without risk. Dilute with water and mop up if water soluble or absorb liquid with a dry, inert, non-combustible, absorbent material such as: sand, diatomaceous earth, vermiculite, or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

### Large Spill

Stop leak if without risk. Move containers from spill area. Prevent run-off to sewers, water courses basements, or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with a dry, inert, non-combustible, absorbent material such as: sand, diatomaceous earth, vermiculite, or other absorbent material and place in container for disposal according to local regulations (see section 13). Dispose via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. If run-off occurs, notify proper authorities as required, that a spill has occurred. Note: see section 1 for emergency contact information and section 13 for waste disposal.

---

## SECTION 7: HANDLING AND STORAGE

---

### Handling

Wear appropriate personal protective equipment (see section 8). Eating, Drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Workers should wash hands and face prior to eating, drinking, and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool, well-ventilated area, away from incompatible materials (see section 10), food and drink. Keep container tightly closed and sealed until ready to use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Other Precautions

Consult local, state and federal hazardous waste regulators before disposing of waste materials.

Can cause skin irritation, eye irritation, and allergic skin reaction. Avoid contact with eyes, skin, and clothing. Wash thoroughly after using. **DO NOT TAKE INTERNALLY! HARMFUL IF SWALLOWED! FOR PROFESSIONAL USE ONLY.** Use protective skin cream such as FEND2 (MSA) where skin contact is likely. Prevent prolonged or repeated breathing of vapor, or spray mists. Liquid penetrated shoes and leather, causing delayed irritation or skin reactions. **KEEP OUT OF REACH OF CHILDREN. DO NOT HANDLE UNTIL THE MANUFACTURER'S INSTRUCTIONS AND SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD!** Contact manufacturer if further information is required.

---

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Exposure Limit(s)

| <u>Components</u> | <u>Basis</u>                      | <u>Authority</u> | <u>Control Parameters</u> |                       |
|-------------------|-----------------------------------|------------------|---------------------------|-----------------------|
| Ethyl Benzene     | Time Weighted Average (TWA):      | OSHA Z1A         | 100 ppm                   | 435 mg/m <sup>3</sup> |
| Ethyl Benzene     | Recommended exposure limit (REL): | NIOSH            | 100 ppm                   | 435 mg/m <sup>3</sup> |
| Ethyl Benzene     | Threshold Limit Value (TLV):      | ACGIH            | 100 ppm                   | 435 mg/m <sup>3</sup> |
| Xylene            | Time Weighted Average (TWA):      | OSHA Z1A         | 100 ppm                   | 435 mg/m <sup>3</sup> |
| Xylene            | Recommended exposure limit (REL): | NIOSH            | 100 ppm                   | 435 mg/m <sup>3</sup> |
| Xylene            | Threshold Limit Value (TLV):      | ACGIH            | 100 ppm                   | 434 mg/m <sup>3</sup> |

**Consult local authorities for acceptable exposure limits.**

### Respiratory Protection

When utilizing this material wear a NIOSH approved cartridge respirator or gas mask suitable to keep airborne mists and vapor concentration below the time-weighted threshold limit values. **WHEN USING IN POORLY VENTILATED OR CONFINED SPACES, USE A FRESH-AIR SUPPLYING RESPIRATOR OR A SELF-CONTAINED BREATHING APPARATUS.**

### Skin Protection

To prevent repeated or prolonged skin contact, wear appropriate safety garments such as impervious gloves, head/neck covers, aprons, jackets, pants, coveralls, and boots. Replace defective PPE and/or spoiled garments/boots.

### Eye Protection

Chemical splash goggles and face shield in compliance with OSHA regulations are advised for eye protection.

### Engineering Controls

Use explosion-proof suction type exhaust fans and blowers with sufficient CFM capacity to keep solvent vapors below 20% of the explosive limit.

Provide sufficient mechanical ventilation to maintain exposure below TLV(s).

### Exposure Guidelines

Consult local authorities for acceptable exposure limits

### Other Protective Clothing or Equipment

Use protective barrier creams on exposed skin areas.

## Work Hygienic Practices

As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, and before eating, drinking, using tobacco products or restrooms. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

|  |  |
|--|--|
| <b>Appearance (physical state, color, etc.):</b>       | Colorless, clear liquid                                      |
| <b>Odor:</b>   | Hydrocarbon  |
| <b>Odor Threshold:</b>                                 | Odor threshold in air is 5x10 <sup>-5</sup> mg/l             |
| <b>pH:</b>   | Not available  |
| <b>Melting Point / Freezing Point:</b>                 | -54°F — -15.07°F (-48°C — -26.15°C)                          |
| <b>Initial Boiling Point and Range:</b>                | 277°F — 284°F (136 — 140° C) at 1,013 hPa (760 mmHg)         |
| <b>Flash Point:</b>                                    | 77° F (25° C) (method: closed cup)                           |
| <b>Evaporation Rate:</b>                               | 13.5 (ether = 1)   |
| <b>Flammability (solid, gas):</b>                      | Not applicable.  |
| <b>Upper/Lower flammability or explosive limits:</b>   | Lower Explosive Limit: 1.1%(V), Upper Explosive Limit: 7%(V) |
| <b>Vapor Pressure:</b>                                 | 24 hPa (18 mmHg) at 37.70° C (99.86° F)                      |
| <b>Vapor Density: (air = 1)</b>                        | 3.7 @ 20 - 25°C (68 - 77°F), (air = 1)                       |
| <b>Relative Density:</b>                               | 0.87 g/cm <sup>3</sup> @ 20 - 25 °C (68 - 77 °F)             |
| <b>Solubility:</b>                                     | Insoluble in water   |
| <b>Partition coefficient: <i>n</i>- octanol/water:</b> | 3.12 – 3.20  |
| <b>Auto-ignition temperature:</b>                      | 809°F – 986°F (432°C - 530°C)                                |
| <b>Decomposition Temperature:</b>                      | Not available.   |
| <b>Volatile Organic Compounds (VOC):</b>               | 7.25 lbs/gal (868.74 g/L)                                    |
| <b>Percent solids by weight:</b>                       | 0.00   |
| <b>Percent solids by volume:</b>                       | 0.00   |
| <b>Specific Gravity:</b>                               | 0.870 @ 70°F (21°C)  |
| <b>Weight per gallon:</b>                              | 7.25   |

---

## SECTION 10: STABILITY AND REACTIVITY

---

### Chemical Stability:

Stable under recommended storage conditions.

### Possibility of hazardous reactions:

Under normal conditions of storage and use, hazardous reactions will not occur.

### Conditions to avoid:

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

### Incompatible materials:

Nitric acid, strong oxidizing agents (e.g. perchloric acid). Not corrosive to metals.

### Hazardous Polymerization:

Under normal conditions of storage and use, hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products:

Very toxic carbon monoxide, carbon dioxide; reactive chemicals; very toxic, flammable aldehydes; and other chemicals.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**Toxicological Information****Likely routes of exposure and potential health effects**

- Inhalation:** May be harmful if inhaled. Causes respiratory tract irritation.  
**Skin:** Causes skin irritation.  
**Eyes:** Causes eye irritation.  
**Ingestion:** May be harmful if swallowed.

**Acute Toxicity Data**

| Product/ingredient name | Method                      | Species | Dose              | Exposure | Result |
|-------------------------|-----------------------------|---------|-------------------|----------|--------|
| Ethyl Benzene           | LD <sub>50</sub> Inhalation | Rat     | No data available | –        | –      |
| Ethyl Benzene           | LC <sub>50</sub> Oral       | Rat     | No data available | –        | –      |
| Ethyl Benzene           | LD <sub>50</sub> Dermal     | Rabbit  | No data available | –        | –      |
| Xylene                  | LC <sub>50</sub> Inhalation | Rat     | No data available | –        | –      |
| Xylene                  | LC <sub>50</sub> Oral       | Rat     | No data available | –        | –      |
| Xylene                  | LD <sub>50</sub> Dermal     | Rabbit  | No data available | –        | –      |

**Potential chronic health effects**

- Chronic effects:** Can cause dry, red, cracked skin (dermatitis) following skin contact. Exposure to this chemical and loud noise may cause greater hearing loss than expected from noise exposure alone. May harm the nervous system. Conclusions cannot be drawn from the limited studies available.
- Target organs:** Liver, Kidney, Blood, Eyes, ears, Heart, Bone marrow, Central nervous system
- IARC:** Group 2B: Possibly carcinogenic to humans (Ethylbenzene)  
**IARC:** Group 3: Not classifiable as to its carcinogenicity to humans (Xylene)
- Carcinogenicity:** **NTP:** No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.  
**OSHA:** No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.  
**EPA** has classified mixed xylenes as a Group D, not classifiable as to human carcinogenicity.
- Mutagenicity:** No data available  
**Teratogenicity:** No data available  
**Fertility effects:** No data available  
**Developmental effects** No data available
- Medical conditions aggravated by over- exposure:** Pre-existing respiratory or skin disorders may be aggravated by over-exposure to this product.

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

**Ecological Information**

**Environmental effects** Toxic to aquatic organisms. May be harmful to the environment if released in large quantities.

**Aquatic Ecotoxicity** No data on specific product

**Ecotoxicity****Aquatic****Toxicity to Fish**

| Product/ingredient name | Test             | Species           | Dose | Exposure |
|-------------------------|------------------|-------------------|------|----------|
| Ethyl Benzene           | LC <sub>50</sub> | No data available | –    | –        |
| Xylene                  | LC <sub>50</sub> | No data available | –    | –        |

**Toxicity to aquatic invertebrates**

| Product/ingredient name | Test             | Species           | Dose | Exposure |
|-------------------------|------------------|-------------------|------|----------|
| Ethyl Benzene           | LC <sub>50</sub> | No data available | –    | –        |
| Xylene                  | LC <sub>50</sub> | No data available | –    | –        |

## Persistence and degradability

| Product/ingredient name | Test              | Concentration | Result |
|-------------------------|-------------------|---------------|--------|
| Ethyl Benzene           | No data available | —             | —      |
| Xylene                  | No data available | —             | —      |

## Bioaccumulative potential

No data available.

## Mobility in soil

No data available.

## Other adverse affects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

### Waste Disposal Method

Consult local, state and federal hazardous waste regulators before disposing of waste materials. The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions, and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. **DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS ONLY.**


---

## 14. TRANSPORT INFORMATION

---

### U.S. DEPARTMENT OF TRANSPORTATION

|                      |  |
|----------------------|--|
| Proper Shipping Name | Xylenes                                      |
| Hazard Class         | 3  |
| ID Number            | UN1307                                       |
| Packing Group        | III  |
| Emergency phone      | +1-352-323-3500 (US Toll Free: 800-535-5053) |



| HMIS |                     |
|------|---------------------|
| 2*   | Health              |
| 3    | Flammability        |
| 0    | Physical Hazard     |
| J    | Personal Protection |



### TRANSPORT CANADA

|                      |  |
|----------------------|--|
| Proper Shipping Name | Xylenes                                      |
| Hazard Class         | 8  |
| ID Number            | UN1307                                       |
| Packing Group        | III  |
| Emergency phone      | +1-352-323-3500 (US Toll Free: 800-535-5053) |

### IMO/IMDG

|                      |  |
|----------------------|--|
| Proper Shipping Name | Xylenes                                      |
| Hazard Class         | 3  |
| ID Number            | UN1307                                       |
| Packing Group        | III  |
| Emergency phone      | +1-352-323-3500 (US Toll Free: 800-535-5053) |
| Stowage Location     | B  |
| EmS Fire / EmS Spill | F-E / S-D                                    |

**IATA/DGR**

|                              |  |  |
|------------------------------|--|--|
| Proper Shipping Name         | Xylenes                                      |  |
| Hazard Class                 | 3  |  |
| ID Number                    | UN1307                                       |  |
| Packing Group                | III  |  |
| Emergency phone              | +1-352-323-3500 (US Toll Free: 800-535-5053) |  |
| Passenger and Cargo Aircraft | Quantity limitation:                         | 1.32 US-Gal (5 L) Packaging instruction: 355   |
| Cargo Aircraft Only          | Quantity limitation:                         | 15.85 US-Gal (60 L) Packaging instruction: N/A |

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

|                              |  |
|------------------------------|--|
| Nombre propio del transporte | Xilenos                                      |
| Clase de peligro             | 3  |
| Número de identificación del | UN1307                                       |
| Grupo de embalaje            | III  |
| teléfono de emergencia       | +1-352-323-3500 (US Toll Free: 800-535-5053) |

***Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.***

**SECTION 15: REGULATORY INFORMATION****U.S. FEDERAL REGULATIONS****U.S. Department of Labor, Occupational Safety & Health Administration (OSHA)**

Hazard Communication Standard (HCS) Classification: See Section 2 above  
 Effective 26 March 2012, OSHA modified its Hazard Communication Standard (HCS), **29 CFR Parts 1910, 1915, and 1926**, to conform to the United Nations' Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

**Emergency Planning and Community Right-to-Know Act (EPCRA)****Sections: 302/304 Extremely Hazardous Substances (EHS):**

No chemicals in this material are subject to reporting requirements of Section 302

Reportable chemicals under Section 304:

| <u>Ingredient(s)</u> | <u>CAS No.</u> |
|----------------------|----------------|
| Ethyl Benzene        | 100-41-4       |
| Xylene               | 1330-20-7      |

**311/312 Hazard Categories**

|             |                                    |     |
|-------------|------------------------------------|-----|
| Category A: | Immediate (Acute) Health Hazard:   | Yes |
| Category D: | Delayed (Chronic) Health Hazard:   | Yes |
| Category F: | Fire Hazard:                       | Yes |
| Category R: | Reactive Hazard:                   | No  |
| Category S: | Sudden Release of Pressure Hazard: | No  |

| <u>Ingredient(s)</u> | <u>CAS No.</u> | <u>Category</u> |
|----------------------|----------------|-----------------|
| Ethyl Benzene        | 100-41-4       | A, D, F         |
| Xylene               | 1330-20-7      | A, D, F         |

**Section: 313 Toxics Release Inventory (TRI) Reportable Ingredients:**

| <u>Ingredient(s)</u> | <u>CAS No.</u> |
|----------------------|----------------|
| Ethyl Benzene        | 100-41-4       |
| Xylene               | 1330-20-7      |



## State Regulations

**USA, CALIFORNIA STATE SAFE DRINKING & TOXIC ENFORCEMENT ACT (PROPOSITION 65):** WARNING! This product contains a chemical known to the State of California to cause cancer.

| <u>Ingredient(s)</u> | <u>CAS No.</u> |
|----------------------|----------------|
| Ethyl Benzene        | 100-41-4       |

### USA, Massachusetts Right-to-Know Components:

| <u>Ingredient(s)</u> | <u>CAS No.</u> |
|----------------------|----------------|
| Ethyl Benzene        | 100-41-4       |
| Xylene               | 1330-20-7      |

### USA, Michigan Right-to-Know Components:

| <u>Ingredient(s)</u> | <u>CAS No.</u> |
|----------------------|----------------|
| Ethyl Benzene        | 100-41-4       |
| Xylene               | 1330-20-7      |

### USA, New Jersey Right-to-Know:

| <u>Ingredient(s)</u> | <u>CAS No.</u> |
|----------------------|----------------|
| Ethyl Benzene        | 100-41-4       |
| Xylene               | 1330-20-7      |

### USA, PENNSYLVANIA RIGHT-TO-KNOW:

| <u>Ingredient(s)</u> | <u>CAS No.</u> |
|----------------------|----------------|
| Ethyl Benzene        | 100-41-4       |
| Xylene               | 1330-20-7      |

PRODUCT SPECIFIC HEALTH AND SAFETY DATA IN OTHER SECTIONS OF THIS MSDS MAY ALSO BE APPLICABLE FOR STATE REQUIREMENTS. FOR DETAILS ON YOUR REGULATORY REQUIREMENTS YOU SHOULD CONTACT THE APPROPRIATE AGENCY IN YOUR STATE.

---

## SECTION 16: OTHER INFORMATION

---

### Preparation Information

This MSDS has been prepared by CORCHEM® Corporation.

Revision: 3-10222014, Product Code: C005-1-0C0

**DISCLAIMER:** All information contained herein is based upon data obtained from CORCHEM's suppliers and/or recognized technical sources.

The data in this MSDS relates only to the specific material designated herein and does not relate to its use in combination with any other material or in any other process.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of CORCHEM® Corporation.

